

SAXOTIG AC/DC TIG machines are designed for the welding specialists. SAXOTIG is the ideal machine to meet the requirements of maintenance applications.

Specification

- Features: User-friendly front panel.
- AC/DC welding currents.
- MMA or 2T-4T TIG and spot mode Selection: pulsed TIG DC, AC with variable frequencies
- and adjustment of the balance cleaning, Time/penetration, Robustness.



Technical features

SAXOTIG 160 AC/DC	
Power supply	1~ 230 V (±10%) 50/60 Hz
Effective primary consumption	13 A
Max primary consumption	23A (TIG)
No load voltage	82 V
Secondary current range	5 - 150 A
DutyCycle 10mn 40°C at 35%	150 A (30%)
DutyCycle 10mn 40°C at 60%	100 A
DutyCycle 10mn 40°C at 100%	80 A
Tool connection	13 mm
Protection index	IP 23
Protection class	H
Dimensions (LxIxH) mm	410 x 220 x 430
Weight kg	21
Standard	EN 60974-1 / EN 60974-10

» Delivery equipment

Primary cable 3,5 m with SCHUKO plug, earth cable 3 m with earth clamp and DINSE connector, equipped gas hose 2 m

» Items codes

W000056009 - SAXOTIG 160 AC/DC
W000242064 - SAXOTIG 160 ACDC/T10/DET

» Options

W000242069 - COMMANDE MANUELLE 10 M
W000241602 - PEDALE DE CAD SAXOTECH
W000375730 - UNIVERSAL TROLLEY UNIVERSAL TROLLEY ALL INVERTER

» Associated tools

W000278353 - PROTIG NG 10 RLS - 5M
W000278355 - PROTIG NG 10 RLS - 8M
W000278356 - PROTIG NG 20 RLS - 5M
W000278357 - PROTIG NG 20 RLS - 8M
W000306441 - WEAR PARTS BOX T10-10W
W000306442 - WEAR PARTS BOX T20
W000306135 - TORCH EXTENSION AIR-S-5B-15M
W000260684 - WELDLINE KIT 25C50

» Environnement & protections

W000276910 - CHAMELEON V0
W000372475 - CHAMELEON 4V 2500
W000010421 - WELDING GLOVES TIG T9