

The air-cooled TIG 17 welding torch is ideal for welders working on a wide range of jobs, guaranteeing consistent, foolproof welding. The highly flexible harness ensures a comfortable grip and easy handling. Interchangeable buttons allow the torch to be adapted to all welders and transformed into a remote control for raising and lowering the welding current (Potentiometer / Up & Down).

MODULAR DESIGN

The control modules can be changed at any time, in a matter of seconds, without the need for tools.



Single button

084247

Double button

084254

Button + Potentiometer

084278

Up & Down

084261

Trigger

089266



Economical and durable thanks to its interchangeable knob

Ergonomically optimised handle for excellent grip

Ball-and-socket cable to reduce wrist twisting

Its protective leather sheath resists abrasion and ensures perfect glide over the forearm.

Cable resistant to daily twisting



Supplied in a coloured box (380 x 310 x 75 mm)

HIGH PERFORMANCE

- Lightweight, easy-to-handle torch.
- Optional sieve diffuser for uniform gas distribution.
- Universal connector (Ø 35/50 mm Amphenol).

FEATURES

Duty cycle	DC	140 A at 35 %
	AC	125 A at 35 %
Cooling	air	
Recommended electrode diameter	1.6 > 4.0 mm	
Original module	Single button	
Beam length	4 m or 8 m	
Torch weight	4 m	1.9 kg
	8 m	3.4 kg

TIG 17

Optional consumables box 044678



CONSUMABLES (options)

				Standard							
Cap (x1)		Vice grip (x3)									
Short	044944	Ø 1.6	044982	045040		Ø 1.6	044968	N4 Ø 6.5	038394	N10 Ø 16	045293
Long	044951	Ø 2.0	044999			Ø 2.0	044975	N5 Ø 8.0	045026	N12 Ø 19	045309
		Ø 2.4	045019			Ø 2.4	044975	N6 Ø 9.5	038400		
		Ø 3.2	045125			Ø 3.2	045118	N7 Ø 11	045033		
		Ø 4.0	047655			Ø 4.0	047648	N8 Ø 12.5	045286		
Pro											
											
Insulating ring (x1)		Diffuser ring (x1)		Screen diffuser (x2)		Diffuser nozzle (x3)					
045040		045095		Ø 1.6 045057 Ø 2.0 045064 Ø 2.4 045064		N5 Ø 8.0 045071 N7 Ø 11 045088					