

REDESIGNED
FOR BETTER PERFORMANCE



DIGISTEEL COMPACT RANGE

250C · 320C
250C PRO · 320C PRO · 380C PRO · 450C PRO



SAF-FRO

www.saf-fro.com

DIGISTEEL COMPACT RANGE

The **DIGISTEEL COMPACTS RANGE** is built on the latest Saf-Fro inverter platform, ensuring optimal **MIG/MAG** and **MMA** welding performance with excellent power and cost efficiency.

The range consists of: 250A, 320A, 380A and 450A power sources with a choice of either the **C** panel (250C & 320C) or the **C PRO** panel (250C PRO, 320C PRO, 380C PRO & 450C PRO), that meet most customers' needs and covers a wide range of welding applications.

The Plug&Play water cooler **COOLARC® 26** is available for **DIGISTEEL 380C PRO & 450C PRO**.

**CHOOSE DIGISTEEL FOR EXCELLENT
AND EFFICIENT MIG/MAG AND MMA WELDING**



C PRO

FULLY SYNERGIC
7" TFT COLOR SCREEN



DIGISTEEL 450C PRO
450A@80%

DIGISTEEL 380C PRO
380A@40%

DIGISTEEL 320C PRO
320A@40%

DIGISTEEL 250C PRO
250A@60%

C

MANUAL MIG
SIMPLE USER INTERFACE



DIGISTEEL 320C
320A@40%

DIGISTEEL 250C
250A@60%




SPECIFICATION

Product	Item Number	Input (V)	Rated Output (A)			Weight (kg)	Dimensions W x L x D (mm)	Protection Class
			100%	60%	40%			
DIGISTEEL 450C PRO	W10000095	400V 3Ph ± 15% 50/60 Hz	420	450 (80%)	–	80,4	560 x 900 x 870	IP23
DIGISTEEL 380C PRO	W10000094		240	320	380	69,2		
DIGISTEEL 320C PRO	W10000093		195	250	320	67	540 x 900 x 870	
DIGISTEEL 250C PRO	W10000091		–					
DIGISTEEL 320C	W10000092		320					
DIGISTEEL 250C	W10000090		–					


Product	Item Number	Input (V)	Cooling power @1l/min (kW)	Reservoir capacity (l)	Maximum Pressure (MPa)	Weight (kg)	Dimensions W x L x D (mm)	Protection Class
COOLARC® 26	K14182-1	230/400V ± 15% 50/60 Hz	0.84	4	0,47	18	260 x 150 x 680	IP23

PREMIUM ARC PERFORMANCE


- **ARC INITIATION** – Repeatable arc ignition with outstanding arc characteristics.
- **ARC STABILITY** – Excellent arc stability, ensuring a smooth droplet transfer with reduced spatter.
- **ARC DYNAMICS** – Rapid parameter adjustment allowing variability under welding conditions.



MIG/MAG Wire



Stick Electrodes



Gouging Electrodes



Processes

- GMAW
- FCAW-G
- FCAW-S
- SMAW
- CAG (only 450C)

Materials

- Steel
- Stainless steel
- Low alloy steel
- Aluminium
- MIG brazing

Applications

- General fabrication
- Construction site
- Maintenance and repair
- Light industrial

NEW! FEATURES

NEW ERGONOMIC HANDLE

For safe movement of the machine and an effortless grip, even when wearing gloves

CABLE MANAGEMENT SYSTEM

(option)
For easy transportation of the whole welding system, (cables, guns, etc.)

NEW ENCODERS

for more precise adjustment



CLOCK & CALENDAR

Weld quality data can also be monitored, logged and recorded using a USB

Start Time	Average WFS (mm/min)	Average current (A)	Average voltage (V)	Arc Time (s)	Mode	Job	Job (Name)
26.09.2020 21:33	149	164	21.13	35	3	-	-
27.09.2020 19:53	149	165	21.23	23	3	-	-
27.09.2020 19:55	149	163	21.35	15	3	-	-
27.09.2020 19:59	149	162	21.16	32	3	-	-
27.10.2020 10:53	6.60	215	23.6	32	12	3	Welder 1
27.10.2020 10:55	6.60	218	23.55	33	12	3	Welder 1
27.10.2020 10:58	6.60	220	23.45	31	12	3	Welder 1
27.10.2020 11:02	6.60	214	23.56	32	12	3	Welder 1
27.10.2020 11:08	6.60	219	23.3	35	12	3	Welder 1
27.10.2020 11:12	4.31	140	20.4	33	12	-	-
27.10.2020 16:15	4.31	140	20.5	15	12	-	-
27.10.2020 16:18	4.31	140	20.3	14	12	-	-
27.10.2020 16:21	4.31	140	20.35	12	12	-	-
27.10.2020 16:25	4.31	140	20.5	14	12	-	-



SPEAKER

Additional audio signals when adjusting the encoders and when any improper operation is selected. Training, advertising and other video displays now also include sound



FUNCTIONALITIES & ERGONOMICS

Ergonomic design

- Tilting gas bottle tray for ease of loading
- Ideal height for easy-to-view settings
- Easy maneuverability and small footprint
- Convenient top-mounted expendable parts compartment



UI protection cover

7" color TFT screen
Simple navigation also when using welding gloves

Rubber bumpers protecting feet
(as standard for 380C & 450C)

4 lifting eyes for easy hook-in and safe transportation

Gun rest

Tools storage

COOL ARC® 26
as option (only for 380C & 450C)

LED lighting inside feeder chamber

Inspection window

Low gas cylinder entry

Large wheels to easily and effortlessly overcome obstacles such as cables or thresholds

STATE OF THE ART TECHNOLOGY IN WIRE FEEDING

Professional wire feeding system – robust and precise

- 4 individually driven rolls for extremely stable wire feeding of various wire types
- Aluminum housing for a long service life
- Big roll diameter (37mm) for optimal wire feeding
- Simple, tool-free roll change
- Factory-fitted with rolls for 1,0 mm and 1,2 mm steel and stainless steel

Steel	3-5
Stainless steel	
Braze	2,5-3,5
Flux cored	
Aluminium	1,5-2,5


Wire feeder pressure set-up




3-5	Steel
	Stainless steel
2,5-3,5	Braze
	Flux cored
1,5-2,5	Aluminium

LED lights:
better visibility


Optimized wire
positioning:
improved arc stability
& reduced gun
vibration




Individually adjustable contact pressure for the front and rear roll pair
Adjustable set-up for aluminium, steel, stainless steel, braze, flux cored wire



V-groove
for stainless steel, steel



U-groove for
aluminium



V-groove, knurled
for flux cored wire

Color-coded for wire diameter differentiation



New locking system, quick exchange of roll and wire guides
Simple, tool-free roll change – just few steps

- 1 Unlock the roll fastener
- 2 Unlock pressure arm
- 3 Exchange the roll



BUILT FOR DEMANDING INDUSTRIAL CONDITIONS

High duty cycle 420A/100% (450C)

- High production efficiency
- Digital arc control
- True Heavy Duty

Inverter engine technology – ECO Friendly

- Lower energy consumption thanks to high efficiency – energy cost saving
- Automatic power-saving modes (standby/shutdown function)
- Generator ready

Lincoln Electric Industrial design – ready to use anywhere

- Safety class IP23, potted PCBs and no structural plastics
- 3 Year full parts and labour warranty



Easy maintenance and servicing

Easy access to internal components
Software update via laptop or USB (Advanced version)

Intelligent F.A.N. (Fan As Needed)



Cooling tunnel design

INNOVATIVE, INTUITIVE USER INTERFACE – REDUCED TIME FOR TRAINING

Simple navigation also when using welding gloves

Innovative and easy communication

- Two controls, one button for easy navigation
- Icon language for key commands
- Easy process and settings selection
- ARCFX™ – joint visualization
- Work point in material thickness (mm) / WFS / A
- Locking function / Limits / Memories / Jobs
- Interface available in languages: English, German, French, Polish, Finnish, Spanish, Italian, Russian, Dutch, Romanian, Slovakian, Hungarian, Czech, Turkish, Portuguese

7" COLOR DISPLAY!

More functions & features

Auto

AUTO-SETTINGS

Preset parameters to increase productivity.



USB CONNECTIVITY

Easy software update & diagnostics, weld log for quality monitoring.

NEW



SPEAKER

Product operation (adjusting the encoders or pressing the button) and errors signaled by a sound.

NEW



CLOCK & CALENDAR

Simple welding quality monitoring as weld log data recording on USB.



STANDARD USER INTERFACE – BASIC SETTINGS

Welding Process & Shielding Gas Selection


- Welding characteristics optimized in terms of welding process (GMAW/FCAW or SMAW) selection and shielding gas type for the best dynamics and minimal spatter
- Simple and quick selection by pressing the button
- LEDs showing the selected process

Easy access to the most commonly used welding parameters:

- **Arc dynamics** (inductance effect – from soft to hard)
- Torch trigger mode 2-step / 4-step
- Wire Feed Speed **Run-in** function
- **Burn-back time**



Welding flowchart for easiest setting of all welding parameters



STANDARD VS ADVANCED – COMPARISON OF FUNCTIONS AND FEATURES



C PRO		C
7" Color TFT	UI type	LED's
✓	Speakers	-
✓	Clock and calendar	-
✓	Display view configuration	-
✓	Auto settings	-
✓ (50)	Memory Jobs	-
✓	Limits	-
✓	Locking function	-
✓	Languages	-
✓	USB connectivity	-
✓	Media files (Support)	-
✓	Weld Logs / History	-
✓	Quick Triger	-
✓	Push-Pull gun	-
✓	Cross-switch gun	-
✓	A/B procedure	-
✓	Software version	✓
✓	Factory Reset	✓
✓	Inductance	✓
✓	2T/4T Gun mode	✓
✓	Spot welding	✓
✓	Gas purge test	✓
✓	Cold Inch test	✓
✓	Preflow time	✓
✓	Run-in WFS	✓
✓	Start procedure	-
✓	Crater procedure	✓
✓	Burnback time	✓
✓	Postflow time	✓
✓	Hot Start (SMAW)	✓
✓	Arc Force (SMAW)	✓
C PRO	Welding Processes	C
✓	GMAW / FCAW	✓
✓	Stick mode	✓
✓	Synergic	-
✓ (450C PRO)	CAG	-



Product	Model	Welding parameters	Setting	Synergic Modes	Support on screen (2)	ARCFX™	Memories / JOBS / Limits	Locking function	USB	Languages selection	Cooler connection	Others
DIGISTEEL 450	C PRO	7 TFT colour screen with ARCFX™	Auto / Manual	33	•	Joint visualization Work point in A/mm	• (49)	•	• Software update Welding Data Collection	•	•	Procedure A/B Quick Trigger Push-Pull Gun
DIGISTEEL 380				28								
DIGISTEEL 320				25								
DIGISTEEL 250				25								
DIGISTEEL 320	C	LEDs meters	Manual	(7) (1)	-	-	-	-	-	-	-	-
DIGISTEEL 250				-	-	-	-	-	-	-	-	-

(1) Welding Process & Shielding Gas Selection: MIG / FCW Manual with MIX, CO2, Ar gas & STICK mode

(2) Technical data, list of accessories, instructions & safety information directly on the screen

COOL ARC® 26

More functions and features



(Back side view)

Built-in handle
for easy transportation

Cooler fully controlled by power source:
AUTO/ON/OFF for better energy savings and extended service life



Coolant filter
keeps coolant clean

LED lights inside reservoir
for clearer visibility of the coolant level

Flow sensor inside
for gun protection



Simple Connection and Easy Installation





New COOL ARC® 26 cooler fully controlled by power source





Cooler Menu is available when cooler is connected

Settings: 3 Modes of operation available:



1. AUTO
2. OFF
3. ON



Filling Procedure
step by step detail filling instruction




LGS2 MIG GUNS

Simple and reliable, this range is adapted to the most common applications.




Wear parts compatible with the most common standard in Europe.



Easy pivoting handle.



Extra-flexible cable.



Extra length rear cable support ensures smooth and consistent wire feeding.



Compliant with the European requirement for MIG guns.

Choose your gun

Rating calculated using CO₂

- Air cooled
- Water cooled
- Dedicated guns

Series	Size	Rate	200A	230A	250A	270A	330A	350A	420A	500A
LGS2	250G	60%	█							
	240G		█							
	360G	█								
	505W	100%	█							

TO ORDER

3 m	4 m	5 m
W10429-25-3M	W10429-25-4M	W10429-25-5M
W10429-24-3M	W10429-24-4M	W10429-24-5M
W10429-36-3M	W10429-36-4M	W10429-36-5M
W10429-505-3M	W10429-505-4M	W10429-505-5M

MODEL	AIR COOLING			WATER COOLING
	LGS2-250G	LGS2-240G	LGS2-360G	LGS2-505W
Duty cycle (CO ₂ shielding gas)	230 A @ 60%	250 A @ 60%	330 A @ 60%	500 A @ 100%
Applications	Thin plates, light fabrication	Thin plates, light fabrication	Vessel manufacture, steel structures	Heavy duty, high production
Wire diameter	Up to 1,2 mm	Up to 1,2 mm	Up to 1,6 mm	Up to 2,4 mm
Original equipment	Contact tip	1,0 mm	1,0 mm	1,2 mm
	Conical nozzle	15 mm	12,5 mm	16 mm

ACCESSORIES

• Optional ✓ Included

		DIGISTEEL					
		450C PRO	380C PRO	320C PRO	250C PRO	320C	250C
		W100000095	W100000094	W100000093	W100000091	W100000092	W100000090
Control panel cover KIT	K14326-1		✓			•	
Bumpers KIT	K14328-1		✓			•	
Polarity change KIT	K14173-1		✓			•	
Cooler COOL ARC® 26	K14182-1		•			-	
Coolant FREEZCOOL 9,6 l	W000010167		•			-	
Cable Management KIT	K14201-1				•		
Gas flow meter KIT	K14175-1				•		
Gas heater harness KIT	K14176-1				•		
12PIN Remote Control KIT	K14290-1			•			-
6-PIN/12-PIN adapter	K2909-1			•			-
Remote control (1POT, required K14290-1 and K2909-1 adapter KITS)	K10095-1-15M			•			-
Remote control MIG 7M (required K14290-1 KIT)	K14091-1			•			-
Water cooled Push-Pull gun LG PPLG405WC 8 m (required K14290-1 kit)	K10413-PPW405-8M		•			-	
PROMIG PP 341 8M (Standard)	W000385860			•			-
PROMIG PP 341 8M (Potentiometer)	W000385861			•			-
PROMIG PP 441W 8M (Standard)	W000385862		•			-	
PROMIG PP 441W 8M (Potentiometer)	W000385863		•			-	
Adapter 12PIN -> 19 PIN	W100000031			•			-
Cable with Electrode holder 400A/70 mm ² – 5 m	E/H-400A-70-5M				•		
Adapter for spool type S300 (300 mm)	K10158				•		
Adapter for spool type S300 (300 mm)	K10158-1				•		
Adapter for spool S200 (200 mm)	R-1019-125-1/08R				•		


ADAPTER FOR SPOOL TYPE S300

K10158-1



PROMIG PP 341

W000385860
W000385861
W000385862
W000385863



ADAPTER FOR SPOOL TYPE S300

K10158

REMOTE CONTROL

K10095-1-15M



6-PIN/12-PIN ADAPTER

K2909-1



ELECTRODE HOLDER

E/H-400A-70-5M



FREEZCOOL

W000010167



COOL ARC® 26

K14182-1

CABLE MANAGEMENT KIT

K14201-1



ACCESSORIES

Wire Guides

Wire Guide Set Blue 0,6-1,6	0744-000-318R
Wire Guide Set Red 1,8-2,8	0744-000-319R
Euro Wire Guide 0,6-1,6	D-1829-066-4R
Euro Wire Guide 1,8-2,8	D-1829-066-5R

Roll Kit for solid wires

Roll Kit 0,6 / 0,8VT F137 4 rolls (green/blue)	KP14150-V06/08
Roll Kit 0,8 / 1,0VT F137 4 rolls (blue/red)	KP14150-V08/10
Roll Kit 1,2 / 1,6VT F137 4 rolls (orange/yellow)	KP14150-V12/16
Roll Kit 1,6 / 2,4VT F137 4 rolls (yellow/grey)	KP14150-V16/24
Roll Kit 0,9 / 1,1VT F137 4 rolls	KP14150-V09/11
Roll Kit 1,4 / 2,0VT F137 4 rolls	KP14150-V14/20

Roll Kit for aluminium wires

Roll Kit 0,6 / 0,8AT F137 4 rolls (green/blue)	KP14150-U06/08A
Roll Kit 0,8 / 1,0AT F137 4 rolls (blue/red)	KP14150-U08/10A
Roll Kit 1,0 / 1,2AT F137 4 rolls (red/orange)	KP14150-U10/12A
Roll Kit 1,2 / 1,6AT F137 4 rolls (orange/yellow)	KP14150-U12/16A
Roll Kit 1,6 / 2,4AT F137 4 rolls (yellow/grey)	KP14150-U16/24A

Roll Kit for cored wires

Roll Kit 1,2 / 1,6RT F137 4 rolls (orange/yellow)	KP14150-V12/16R
Roll Kit 1,4 / 2,0RT F137 4 rolls	KP14150-V14/20R
Roll Kit 1,6 / 2,4RT F137 4 rolls (yellow/grey)	KP14150-V16/24R
Roll Kit 0,9 / 1,1RT F137 4 rolls	KP14150-V09/11R
Roll Kit 1,0 / 1,2RT F137 4 rolls (-/orange)	KP14150-V10/12R



Each item # contains:

- metal wire guide for Euro socket
- 4 rolls
- plastic wire guide set



www.saf-fro.com

CUSTOMER ASSISTANCE POLICY

The business of Lincoln Electric is manufacturing and selling high quality welding equipment, consumables, and cutting equipment. Our challenge is to meet the needs of our customers and to exceed their expectations. On occasion, purchasers may ask Lincoln Electric for information or advice about their use of our products. Our employees respond to enquiries to the best of their ability based on information provided to them by the customers and the knowledge they may have concerning the application. Our employees, however, are not in a position to verify the information provided or to evaluate the engineering requirements for the particular weldment. Accordingly, Lincoln Electric does not warrant or guarantee or assume any liability with respect to such information or advice. Moreover, the provision of such information or advice does not create, expand, or alter any warranty on our products. Any express or implied warranty that might arise from the information or advice, including any implied warranty of merchantability or any warranty of fitness for any customers' particular purpose is specifically disclaimed.

Lincoln Electric is a responsive manufacturer, but the selection and use of specific products sold by Lincoln Electric is solely within the control of, and remains the sole responsibility of the customer. Many variables beyond the control of Lincoln Electric affect the results obtained in applying these types of fabrication methods and service requirements.

Subject to Change – This information is accurate to the best of our knowledge at the time of printing. Please refer to www.lincolnelectriceurope.com for any updated information.